Department of Labor & Industries Factory Assembled Structures PO Box 44430 Olympia WA 98504-4430



LOW VOLTAGE FIRE/INTRUSION ALARM CHECKLIST

This checklist is designed to be generic in content and may not include all requirements for your particular installation. Manufacturer's installation instructions must be adhered to <u>and available to the inspector at the time of the inspection.</u>

REFERENCE		<u>COMPI</u> YES	<u>JANCE</u> NO
WAC 296-150M	Alteration permit purchased and insignia issued.		
RCW 18.27.200	Contractor doing work is registered.		
HUD 3280.305	No holes bored in floor joist within 2" of top or bottom.		Q
HUD 3280.307d	Exterior surfaces shall be sealed to resist the entrance of rodents.		
HUD 3280.903	Protection from transportation shock and vibration.		
NEC 110-36	All equipment shall be installed per specs.		
NEC 725-6	Equipment to be bonded to frame. Bonding at frame to include a star washer.		
NEC 725-7	All installations shall be in a workmanship-like manner.		
NEC 725-8-6	Conductors shall be protected from physical damage.		
NEC 725-41	Installation for a Class 2 circuit.		
NEC 725-51	Circuit breaker for the transformer to be sized per manufacturer's instructions.		
WAC 296-150M	Re-inspection fee charged if applicable.		
Comments:			***************************************
		·····	······
		•••••	

NOTE: UNLESS OTHERWISE SPECIFIED IN CODE, THE MANUFACTURER'S INSTALLATION INSTRUCTIONS MUST BE FOLLOWED.